

S-150C WORKS

S-150 Trail / Enduro Suspension - 150mm

SRP £4,999

Product Code - WS150CW(size)V2



	Colour	Matt Granite with Burnt Orange / Khaki		
	Sizes Available	M,L,XL		
	Frame	Carbon, Uni-directional Multi Monocoque Front Triangle with Internal Cable Routing, Tapered Head Tube, Intergrip Seat Clamp System, ISCG 5 Guide Mounts, Alloy Symmetrical SCR Rear Triangle and 148mm Boost Dropouts		
✓	✓	Fork	RockShox Pike Ultimate RCT3 29", 150mm Travel, 42mm Offset, DebonAir, Charger 2 RCT3 Damper with 3-Pos Compression Adjust, Fast Black Coating, Tapered Steerer, 110mm x 15mm Boost, Maxle Ultimate	
✓	✓	Rear Shock	RockShox Super Deluxe Plus Ultimate RCT, DebonAir, Fast Black Coating, Adjustable Rebound and 3 Position Compression	
		Headset	FSA No. 42 Orbit ZS Plus, Integrated, 1 1/2" Lower and 1 1/8" Upper Sealed Cartridge Bearings	
	✓	Rear Hub	Hope Pro 4, Sealed Stainless Steel Cartridge Bearings, 12mm x 148mm Boost Through Axle, 28 Hole	
	✓	Front Hub	Hope Pro 4, Sealed Stainless Steel Cartridge Bearings, 15mm x 110mm Boost Through Axle, 28 Hole	
	✓	Spokes	DT Swiss Competition Butted 2.0-1.8-2.0mm, Black Stainless, Brass Nipples	
	✓	Rims	Whyte 30mm Carbon Hookless, Tubeless Ready, 3M Rim Strip with Tubeless Valves Included, 28 Hole	
		Tyres	Maxxis High Roller II WT, TR, 29" x 2.5" 60TPI, EXO Sidewall Protection, 3C Maxx Terra, Front, Maxxis Aggressor WT, TR, 29" x 2.5" 60TPI, EXO Sidewall Protection, Dual Compound, Rear	
	✓	Shift Levers	SRAM XD1 Eagle, MMX, 12 Speed	
		Front Derailleur	N/A	
	✓	Rear Derailleur	SRAM XX1 Eagle, 12 Speed	
	✓	Cassette	SRAM XG-1295 Eagle, 10-50, 12 Speed	
	✓	Chain	SRAM Eagle, 12 Speed	
	✓	✓	Crankset	SRAM Descendant Carbon Eagle, X-SYNC 2, Direct Mount 32T, DUB, 170mm, Boost, 12 Speed
	✓		Bottom Bracket	SRAM DUB, BSA, 73mm
	✓		Seatpost	Bike Yoke Revive, 30.9mm, 160mm Travel, Trigger Remote with MMX attachment
	✓		Seat	Whyte Custom, Dual Density, Triple Panel Design
	✓	✓	Bar	RaceFace NEXT R Carbon, 20mm Rise, 35mm Bar Bore, 800mm Wide
	✓		Stem	Whyte Gravity Stem, 35mm Bar Bore, 40mm Extension
			Grips	Whyte Lock-on V Grip
	✓	✓	Front Brakes	SRAM Guide G2 RSC, 4 Pot, 200mm Rotor
		✓	Rear Brakes	SRAM Guide G2 RSC, 4 Pot, 180mm Rotor
	✓	✓	Brake Levers	SRAM Guide G2 RSC, MMX
			Pedals	None
✓	Indicates an upgrade or improvement over previous version			
✓	Indicates an upgrade or improvement over the model below			

Our Whyte Enduro team have a secret weapon - the S-150 Works is their bike of choice for the more all-round events.

There is a wish list spec on the Works, but stand-outs must include the 30mm hookless Whyte carbon rims hand-laced onto Hope Pro4 hubs, Bike Yoke Revive dropper post with its super-low stack height, and a RockShox Super Deluxe Select + rear shock.

S stands for Switch - the ability to fit 650b wheels with 2.8" tyres and still have UK levels of mud clearance. Our wheel kits switch into your bike in the time it takes to go back to your car and change the Eagle cassette.

Dropout Code	DROPWH18
Shock Stroke and Sag Setting	55mm, Sag 14mm (25%) to 17mm (30%)
Reducer Bush Widths	22mm x 8mm, no hardware at the rear
Eye to Eye Length	210mm

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
M	65.6	75	623	341.5	838
L	65.6	75	640	341.5	863
XL	65.6	75	659	341.5	869
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
M	1211	435	30.9	110	431.8
L	1228	435	30.9	120	457.2
XL	1248	435	30.9	130	482.6

S-150C WORKS

S-150 Trail / Enduro Suspension - 150mm

SRP £4,999

Product Code - WS150CW(size)V2

ADDITIONAL SPECIFICATION & REPLACEMENT PARTS

Top Tube	High Modulus Uni-Directional Carbon
Down Tube	High Modulus Uni-Directional Carbon
Rear Stays	6061 Alloy Double Butted
Paint Code	WAMTU017
Freehub Part Code	HOPE Pro 4
Rear Hub Bearings	Hope
Front Hub Bearings	Hope
Suspension Bearings	WB0025 X 10
Headset Bearings	HS003 (FSA No42)
Headset Code	
Bottom Bracket	BSA SRAM DUB, 73mm
ISG Chainguide Compatibility	
ICR Grommets	1 x WHYICR18-3, 2 x WHYICR18-1
Brake Mount Adaptor	WHYFM180
Spoke Lengths	291 x 290mm (front) 291 x 289mm (rear)
Max Chain Ring Size	
Chain Length for the stock chainring	116
Tubeless Status	Tubeless Ready Rims
Max Tyre Size	29 X 2.8 / 29 X 2.6 Rear
Max Tyre Size with Mudguards	N/A
Mudguard Code	N/A
Rack Compatible	N/A
Kickstand Compatible	N/A
Chain Guide Code	WAMCG1
Rear Thru-Axle Length	M12 X 1.5, 180mm Long
Downtube Protector	WHYPRO11
Chainstay Protector	WHYPRO07
Seat Post Seal	WHYPOSTSEAL 3/4/5
Kitbox Contents	