

TECHNICAL SPECS

Frame

Crafty 6061 Alloy Stealth Evo, e-Bike Optimized Zero Suspension System, 150mm travel, Forward Geometry, internal removable battery with integrated alloy cover, Boost 12x148mm rear axle, tapered head tube, one-piece Monoblock upper link, HHG internal cable routing, MAX capacity sealed bearings, oversize 17mm axles, integrated dropout speed sensor, exclusive plastic motor covers.

Sizes

S: 380mm / M: 420mm / L: 450mm / XL: 490mm

Rear shock

Fox Float DPX2 LV EVOL Factory Kashima, 205x65mm. Settings: compression 3 positions lever, low-speed compression, low-speed rebound, air preload. Trunion top mount, 25x10mm bottom bushings

Shock settings

CEC001 compression, Medium rebound, 0.2 volume spacer

Fork

Fox 38 29 Float FIT4 EVOL Factory Kashima, 160mm, e-bike tuned, tapered steerer tube, Boost 15x110mm axle, offset 44mm. Settings: 3 positions with micro adjust compression, low-speed rebound, air preload

Headset

Onoff Saturn tapered for 1-1/8" to 1-1/2" head tube, ACB sealed bearings, top 41x30.2x7x45°x45°, bottom 51.9x40x8x45°x45°

Stem

Onoff Sulfur FG 30mm 0°, 6061 forged alloy, 31.8mm barbore

Handlebar

Onoff Sulfur 1.0 double butted 6061 alloy, rise: 20mm, width: 780mm, 9° backsweep, 5° upsweep, 31.8mm barbore

Grips

Onoff Desert, 1lock-on, 135mm, sizes: S/M L/XL

Seatpost

Onoff Pija dropper internal, diameter 31.6mm, S size: 387x125mm, M size: 425x150mm, L/XL size: 465x170mm

Saddle

SDG BEL-AIR 3.0, EVA foam, Alloy rails

Front brake

Sram Code R, oversized 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed metal sintered pads

Rear brake

Sram Code R, oversized 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed metal sintered pads

Brake lever

Sram Code R, tool-free reach adjust

Rims

DT Swiss H1900 Spline 29, 30mm internal width, sleeved aluminum, tubeless ready, 28 spokes

Spokes

DT Hybrid SP, straightpull

Front hub

DT 370, Boost 15x110mm, IS 6 bolts

Rear hub

DT 370, Boost 12x148mm, 3 Pawl system, IS 6 bolts

Front tire

Maxxis Minion DHF 29x2.6, tubeless ready, 3C MAXX TERRA, EXO+ Protection, 120TPI, folding bead

Rear tire

Maxxis Minion DHR II 29x2.6, tubeless ready, 3C MAXX TERRA, EXO+ Protection, 120TPI, folding bead

Crankset

Race Face Aeffect ebike, 165mm

Rings

Sram X-Sync 2 Eagle 34T, steel, narrow-wide, 104 BCD

Chain

Sram NX Eagle, 12s, Powerlock

Rear deraillieur

Sram GX Eagle, Type 3 roller bearing clutch, cage lock, 1x12s, X-Actuation 1:1

Shift levers

Sram Trigger GX Eagle, 12s, X-Actuation 1:1, single click

Cassette

Sram XG-1230, 11-50T, 12s

Derailleur hanger

Mondraker M068

Weight

24.6 kg

Display

Bosch Kiox

Motor

Bosch Performance Line CX Cruise (25Km/h) GEN4

Battery

Bosch Powertube 625Wh