

COMPONENTS

TECHNICAL SPECS

frame

Frame

Chaser 6061 Alloy Stealth Evo, e-Bike Optimized Zero Suspension System, 150mm travel, Forward Geometry, internal removable battery, Boost 12x148mm rear axle, tapered head tube, one-piece Monoblock upper link, HHG internal cable routing, MAX capacity sealed bearings, oversize 17mm axles, integrated dropout speed sensor, exclusive plastic motor covers, shock mudguard

sizes

Sizes

S: 380mm / M: 420mm / L: 450mm / XL: 490mm

rear shock

Rear shock

RockShox Deluxe Select R DebonAir, 205x65mm. Settings: Low-speed rebound, air preload. Trunnion top mount, 25x10mm bottom bushings

shock settings

Shock settings

DebonAir Progressive, Light compression, Linear rebound, 1 Token

fork

Fork

RockShox 35 Silver TK 29, 160mm, TurnKey, Solo Air, tapered steerer tube, Boost 15x110mm axle, 35mm steel stanchions, 44mm offset. Settings: compression adjustment at low-speed to lock, rebound, air preload

headset

Headset

Onoff Saturn tapered for 1-1/8" to 1-1/2" head tube, ACB sealed bearings, top 41x30.2x7x45°x45°, bottom 51.9x40x8x45°x45°

stem

Stem

Onoff Sulfur FG 30mm 0°, 6061 forged alloy, 31.8mm bar bore

handlebar

Handlebar

Onoff Sulfur 1.0 double butted 6061 alloy, rise: 20mm, width: 800mm, 9° backsweep, 5° upsweep, 31.8mm bar bore

grips

Grips

Onoff Twin, 1 lock-on, 135mm

seatpost	Rims
Seatpost	MDK-HP1 29, 30mm internal width, tubeless ready, 32 spokes
Onoff Pija dropper internal, diameter 31.6mm, S size: 405x95-125mm, M size 458x120-150mm, L size: 498x140-170mm, XL size: 498x140-170mm	spokes
	Spokes
saddle	CN round stainless steel
Saddle	
MDK ebike black	front hub
	Front hub
front brake	
Front brake	Formula DC711, Boost 15x110mm, sealed bearings, IS 6 bolts
Sram DB8, 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed organic pads	rear hub
	Rear hub
rear brake	
Rear brake	Formula EHL148 Boost 12x148mm, sealed bearings, IS 6 bolts
Sram DB8, 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed organic pads	front tire
	Front tire
brake lever	
Brake lever	Maxxis Rekon 29x2.6, tubeless ready, dual compound, EXO protection, 60TPI, folding bead
Sram DB8, tool reach adjust	rear tire
	Rear tire
rim	

Maxxis Rekon 29x2.6, tubeless ready, dual compound, EXO protection, 60TPI, folding bead

cassette
Cassette

crankset
Crankset

Sram PG-1210, 11-50T, 12s

Race Face Aeffect ebike, 165mm

derailleur hanger
Derailleur hanger

rings
Rings

Mondraker M068

Sram X-Sync 2 Eagle 34T, steel, narrow-wide, 104 BCD

weight
Weight

chain
Chain

25,2 kg

Sram SX Eagle, 12s, Powerlock

display
Display

rear derrailleur
Rear derrailleur

Bosch Kiox 300 / Bosch Led Remote

Sram SX Eagle, Type 3 roller bearing clutch, cage lock, long cage, 1x12s, X-actuation 1:1

motor
Motor

shift levers
Shift levers

Bosch Performance Line CX (25km/h) Smart System

Sram Trigger SX Eagle, 12s, X-Actuation 1:1, single click

battery
Battery

Bosch Powertube 625Wh