

## COMPONENTS

### TECHNICAL SPECS

- 

#### **Frame**

Raze 29 Stealth Air full Carbon, Zero Suspension System, 130mm travel, Forward Geometry, Carbon Monoblock upper link, Boost 12x148mm rear axle, tapered head tube, 73mm BSA bottom bracket, dedicated 1x drivetrain design, HHG internal cable routing, Enduro MAX sealed bearings, shock mudguard, ISCG 05, custom frame protectors.

#### **Sizes**

S: 380mm / M: 420mm / L: 450mm / XL: 500mm

- 

#### **Rear shock**

Fox Float DPS LV EVOL Performance, 205x57.5mm. Settings: rebound, 3-position compression adjustment (Open/Mid/Lock), air preload. Trunion top mount, 30x8mm bottom bushings

#### **Shock settings**

Light compression, light rebound, air volume spacer 0.6

- 

#### **Fork**

Fox 36 29 Float GRIP EVOL Performance, 150mm, tapered steerer tube, Boost 15x110mm axle, 44mm offset. Settings: 3 positions with micro adjust compression, low-speed rebound, air preload

#### **Headset**

Acros custom for 1-1/2" head tube, angular contact bearings 40x52x7, Internal cable routing

- 

### **Stem**

Onoff Sulfur FG 30mm 0°, 6061 forged alloy, 31.8mm barbore

### **Handlebar**

Onoff Sulfur 1.0 double butted 6061 alloy, rise: 20mm, width: 800mm, 9° backsweep, 5° upsweep, 31.8mm barbore

- 

### **Grips**

Onoff Diamond, 1lock-on, 135mm

### **Seatpost**

Onoff Pija dropper internal, diameter 31.6mm, S size: 387x125mm, M size: 425x150mm, L/XL size: 465x170mm

- 

### **Saddle**

Fizik Antares R7

### **Front brake**

Sram G2, 4-piston caliper, Centerline 180mm IS 6 bolts one-piece rotor, steel-backed organic pads

- 

### **Rear brake**

Sram G2, 4-piston caliper, Centerline 180mm IS 6 bolts one-piece rotor, steel-backed organic pads

**Brake lever**

Sram G2, SwingLink, tool-free reach adjust

- 

**Rims**

DT Swiss XM1700 Spline 29, 30mm internal width, welded aluminum, tubeless ready, 28 spokes

**Spokes**

DT Competition, straightpull

- 

**Front hub**

DT 350, Boost 15x110mm, IS 6 bolts

**Rear hub**

DT 350, Boost 12x148mm, 36T SL Ratchet system, IS 6 bolts, XD freehub

- 

**Front tire**

Maxxis Dissector 29x2.4 WT, tubeless ready, 3C MAXX TERRA compound, EXO+ protection, 120TPI, folding bead

**Rear tire**

Maxxis Aggressor 29x2.3, tubeless ready, dual compound, Exo protection, 60TPI, folding bead

-

## **Crankset**

Truativ Stylo 7k Eagle, Boost, DUB axle, Direct mount chain ring, S/M size: 170mm, L/XL size: 175mm

## **Rings**

32T, CNC-machined alloy, X-SYNC 2

- 

## **Bottom bracket**

Sram DUB BSA, sealed bearings, 73mm

## **Chain**

Sram NX Eagle, 12s, Powerlock

- 

## **Rear derrailleur**

Sram GX Eagle, Type 3 roller bearing clutch, cage lock, 1x12s, X-Actuation 1:1

## **Shift levers**

Sram Trigger NX Eagle, 12s, X-Actuation 1:1

- 

## **Casette**

Sram XG-1275, 10-52T, 12s

## **Derrailleur hanger**

Sram UDH

- 

**Weight**

13.2 kg