

COMPONENTS

TECHNICAL SPECS

frame

Frame

Prime 6061 Xtralite Full Butted Alloy, Forward Geometry, internal battery, tapered head tube, Boost 12x148mm rear axle, integrated dropout speed sensor

sizes

Sizes

XS: 380mm / S: 390mm / M: 430mm / L: 470mm / XL: 510mm

fork

Fork

RockShox 35 Silver TK 29, 100mm, TurnKey, Solo Air, tapered steerer tube, Boost 15x110mm axle, 35mm steel stanchions, 44mm offset. Settings: compression adjustment at low-speed to lock, rebound, air preload

headset

Headset

ONOFF Saturn tapered for 1-1/8" to 1-1/2" head tube, ACB sealed bearings, top 41x30.2x7x45°x45°, bottom 51.9x40x8x45°x45°

stem

Stem

ONOFF Sulfur FG 30mm 0°, 6061 forged alloy, 31.8mm bar bore

handlebar

Handlebar

ONOFF Sulfur 1.0 double butted 6061 alloy, rise: 20mm, width: 800mm, 9° backsweep, 5° upsweep, 31.8mm bar bore

grips

Grips

ONOFF Diamond, 1lock-on, 135mm

seatpost

Seatpost

ONOFF Pija dropper internal, diameter 31.6mm, S size: 387x125mm, M size: 425x150mm, L/XL size: 465x170mm

saddle

Saddle

FIZIK Terra Aidon X5 145mm

front brake

Front brake

SRAM G2 R, 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed organic pads

rear brake

Rear brake

SRAM G2 R, 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed organic pads

brake lever

Brake lever

SRAM G2 R, tool-free reach adjust

rims

Rims

MDK-HP1 29, 30mm internal width, tubeless ready, 32 spokes

spokes

Spokes

CN round stainless steel

front hub

Front hub

Formula DC711, Boost 15x110mm, sealed bearings, IS 6 bolts

rear hub

Rear hub

Formula EHL148 Boost 12x148mm, sealed bearings, IS 6 bolts

front tire

Front tire

Maxxis Grifter 29x2.5, single compound, 60TPI, wire bead, tanned wall.

rear tire

Rear tire

Maxxis Grifter 29x2.5, single compound, 60TPI, wire bead, tanned wall.

crankset

Crankset

Race Face Aeffect ebike, 165mm

rings

Rings

SRAM X-Sync 2 Eagle 34T, steel, narrow-wide, 104 BCD

chain

Chain

SRAM SX Eagle, 12s, Powerlock

rear derrailleur

Rear derrailleur

SRAM SX Eagle, Type 3 roller bearing clutch, cage lock, long cage, 1x12s, X-actuation 1:1

shift levers

Shift levers

SRAM Trigger SX Eagle, 12s, X-Actuation 1:1, single click

cassette

Cassette

SRAM PG-1210, 11-50T, 12s

derailleur hanger

Derailleur hanger

Mondraker M068

others

Others

Front light: 50LUX output DC 6-12V, waterproof Alloy cage. Rear Light: Fender Mount, w/ Reflective, e-bike version, 6-12V. Fenders: Alloy black MDK custom fenders. Rack: Alloy MDK rear Rack, Max loading 25kg. Kickstand: Massload KSA18-40

weight

Weight

24.7 kg

display

Display

Bosch Kiox 300

motor

Motor

Bosch Performance Line CX Cruise (25Km/h) Bosch Smart System

battery

Battery

Bosch Powertube 750Wh