

COMPONENTS

TECHNICAL SPECS

frame

Frame

Raze 29 6061 Alloy Stealth Evo, hydroformed tubing, Zero Suspension System, 130mm travel, Forward Geometry, one piece Monoblock upper link, Boost 12x148mm rear axle, tapered head tube, 73mm BSA bottom bracket, dedicated 1x drivetrain design, telescopic seatpost internal routing, MAX capacity sealed bearings, ISCG 05

sizes

Sizes

S: 380mm / M: 420mm / L: 470mm / XL: 510mm

rear shock

Rear shock

Fox Float DPS LV EVOL Performance, 205x57.5mm. Settings: rebound, 3-position compression adjustment (Open/Mid/Lock), air preload. Trunnion top mount, 25x8mm bottom bushings

shock settings

Shock settings

Light compression, light rebound, air volume spacer 0.6

fork

Fork

RockShox 35 Gold 29 RL, 150mm, Solo Air, tapered steerer tube, Boost 15x110mm axle, 35mm steel stanchions, 44mm offset. Settings: compression adjustment at low-speed to lock, rebound, air preload

headset

Headset

ONOFF Saturn tapered for 1-1/8" to 1-1/2" head tube, ACB sealed bearings, top 41x30.2x7x45°x45°, bottom 51.9x40x8x45°x45°

stem

Stem

ONOFF Sulfur FG 30mm 0°, 6061 forged alloy, 31.8mm barbore

handlebar

Handlebar

ONOFF Sulfur 1.0 double butted 6061 alloy, rise: 20mm, width: 800mm, 9° backsweep, 5° upsweep, 31.8mm barbore

grips

Grips

ONOFF Twin, 1lock-on, 135mm

seatpost	Rims
Seatpost	MDK-EP1 29, 30mm internal width, tubeless ready, 32 spokes
ONOFF Pija dropper internal, diameter 31.6mm, S size: 405x95-125mm, M size 458x120-150mm, L size: 498x140-170mm, XL size: 498x140-170mm	spokes
	Spokes
saddle	CN round stainless steel
Saddle	
MDK series PU 2023	front hub
	Front hub
front brake	
Front brake	Formula DC711, Boost 15x110mm, sealed bearings, IS 6 bolts
Sram Level T, 2 piece caliper, Centerline 180mm IS 6 bolts one-piece rotor, steel-backed organic pad	rear hub
	Rear hub
rear brake	
Rear brake	Formula DHT148 Boost 12x148mm, sealed bearings, IS 6 bolts
Sram Level T, 2 piece caliper, Centerline 180mm IS 6 bolts one-piece rotor, steel-backed organic pad	front tire
	Front tire
brake lever	
Brake lever	Maxxis Dissector 29x2.4 WT, tubeless ready, 3C MAXX TERRA compound, EXO+ protection, 120TPI, folding bead
Sram Level T, Direct Link actuation, tooled reach adjust, lever pivot bushings	rear tire
	Rear tire
rim	

Maxxis Aggressor 29x2.3, tubeless ready, dual compound, Exo protection, 60TPI, folding bead

crankset

Crankset

Sram SX Eagle, Boost, DUB axle, Direct Mount chain ring, S/M size: 170mm, L/XL size: 175mm

rings

Rings

32T, steel, X-Sync 2

bottom bracket

Bottom bracket

Sram DUB BSA, sealed bearings, 73mm

chain

Chain

Sram SX Eagle, 12s, Powerlock

rear derrailleur

Rear derrailleur

Sram SX Eagle, Type 3 roller bearing clutch, cage lock, long cage, 1x12s, X-actuation 1:1

shift levers

Shift levers

Sram Trigger SX Eagle, 12s, X-Actuation 1:1

casette

Casette

Sram PG-1210, 11-50T, 12s

derrailleur hanger

Derrailleur hanger

Sram UDH

weight

Weight

15.9 kg