

## [Detailed description](#)

- 

### **Frame**

Crusher Stealth Air Carbon front triangle, Stealth Alloy rear triangle, e-Bike Optimized Zero Suspension System, 150mm travel, Forward Geometry, integrated internal non-removable battery, Boost 12x148mm rear axle, tapered head tube, one-piece Monoblock upper link, HHG internal cable routing, MAX capacity sealed bearings, oversize 17mm axles, integrated dropout speed sensor, exclusive plastic motor covers.

### **Sizes**

S: 380mm / M: 420mm / L: 450mm / XL: 490mm

### **Rear shock**

Fox Float-X LV Performance, 205x65mm. Settings: compression 2 positions lever, low-speed rebound, air preload. Trunnion top mount, 25x10mm bottom bushings

### **Shock settings**

medium compression, medium rebound, air volume spacer 0.2

### **Fork**

Fox 38 29 Float FIT GRIP EVOL Performance, 160mm, e-bike tuned, tapered steerer tube, Boost 15x110mm axle, 44mm offset. Settings: 3 positions with micro adjust compression, low-speed rebound, air preload

### **Headset**

Acros AZF-601 R1 Block Lock 120°, ZS44/28.6 top, ZS56/40 bottom

### **Stem**

Onoff Sulfur FG 30mm 0°, 6061 forged alloy, 31.8mm barbare

### **Handlebar**

Onoff Sulfur 1.0 double butted 6061 alloy, rise: 20mm, width: 800mm, 9° backsweep, 5° upsweep, 31.8mm barbare

### **Grips**

Onoff Desert, 1lock-on, 135mm

### **Seatpost**

Onoff Pija dropper internal, diameter 31.6mm, 1X Remote lever with bearing, S size: 405x95-125mm, M size: 458x120-150mm, L size: 498x140-170mm, XL size: 558x170-200mm

### **Saddle**

FIZIK Terra Aidon X5 145mm

### **Front brake**

Sram DB8, 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed organic pads

### **Rear brake**

Sram DB8, 4-piston caliper, Centerline 200mm IS  
6 bolts one-piece rotor, steel-backed organic pads

### **Brake lever**

Sram DB8, tool reach adjust, lever pivot bushings

### **Rims**

Mavic E-Deemax 29, 30mm internal width,  
welded, PFP, tubeless ready, 28 spokes

### **Spokes**

Mavic J-bend double butted, contactless lacing

- 

### **Front hub**

Mavic, Boost 15x110mm, IS 6 bolts

### **Rear hub**

Mavic, Boost 12x148mm, ID360 Ratchet system,  
IS 6 bolts, HG freehub

### **Front tire**

Maxxis Minion DHF 29x2.6, tubeless ready, 3C  
MAXX TERRA, EXO+ Protection, 120TPI, folding  
bead

### **Rear tire**

Maxxis Minion DHR II 29x2.6, tubeless ready, 3C  
MAXX TERRA, EXO+ Protection, 120TPI, folding  
bead

### **Crankset**

Shimano Steps FC-EM600 ebike, 165mm

### **Rings**

Sram X-Sync 2 Eagle 34T, alloy, narrow-wide, 104  
BCD

### **Chain**

Sram SX Eagle, 12s, Powerlock

### **Rear derailleur**

Sram GX Eagle, Type 3 roller bearing clutch, cage  
lock, 1x12s, X-Actuation 1:1

### **Shift levers**

Sram Trigger NX Eagle, 12s, X-Actuation 1:1, single  
click

### **Cassette**

Sram PG-1210, 11-50T, 12s

### **Derailleur hanger**

Mondraker M068

**Weight**

24,6 kg

**Display**

Shimano EN600

**Motor**

Shimano STEPS EP801

**Battery**

Simplo internal 720Wh G3