

-

Frame

Raze 29 6061 Alloy Stealth Evo, hydroformed tubing, Zero Suspension System, 130mm travel, Forward Geometry, one piece Monoblock upper link, Boost 12x148mm rear axle, tapered head tube, 73mm BSA bottom bracket, dedicated 1x drivetrain design, telescopic seatpost internal routing, MAX capacity sealed bearings, ISCG 05

Sizes

S: 380mm / M: 420mm / L: 470mm / XL: 510mm

-

Rear shock

Fox Float EVOL Performance, 205x57.5mm. Settings: 2-position compression adjustment (Open/Firm), rebound, air preload. Trunnion top mount, 25x8mm bottom bushings

Shock settings

Light compression, light rebound, air volume spacer 0.6

-

Fork

RockShox 35 Gold 29 RL, 150mm, Solo Air, tapered steerer tube, Boost 15x110mm axle, 35mm steel stanchions, 44mm offset. Settings: compression adjustment at low-speed to lock, rebound, air preload

Headset

Onoff Saturn tapered for 1-1/8" to 1-1/2" head tube, ACB sealed bearings, top 41x30.2x7x45°x45°, bottom 51.9x40x8x45°x45°

-

Stem

Onoff Sulfur FG 30mm 0°, 6061 forged alloy, 31.8mm barbare

Handlebar

Onoff Sulfur 1.0 double butted 6061 alloy, rise: 20mm, width: 800mm, 9° backsweep, 5° upsweep, 31.8mm barbare

-

Grips

Onoff Twin, 1lock-on, 135mm

Seatpost

Onoff Pija dropper internal, diameter 31.6mm, 1X Remote lever with bearing, S size: 405x95-125mm, M size: 458x120-150mm, L size: 498x140-170mm, XL size: 558x170-200mm

-

Saddle

Mondraker MDK Series, SRX, steel rail

Front brake

Sram Level T, 2 piece caliper, Centerline 180mm IS 6 bolts one-piece rotor, steel-backed organic pad

•

Rear brake

Sram Level T, 2 piece caliper, Centerline 180mm IS 6 bolts one-piece rotor, steel-backed organic pad

Brake lever

Sram Level T, Direct Link actuation, tooled reach adjust, lever pivot bushings

•

Rims

Mavic CrossRide 29 Boost, 30mm internal width, tubeless ready, 28 spokes

Spokes

Mavic 28 round j-bend stainless steel

•

Front hub

Mavic Boost 15x110mm, sealed bearings, IS 6 bolts

Rear hub

Mavic ID360 freewheel technology, Boost 12x148mm, IS 6 bolts, HG freehub

•

Front tire

Maxxis Dissector 29x2.4 WT, tubeless ready, 3C MAXX TERRA compound, EXO+ protection, 120TPI, folding bead

Rear tire

Maxxis Aggressor 29x2.3, tubeless ready, dual compound, Exo protection, 60TPI, folding bead

•

Crankset

Sram SX Eagle, Boost, DUB axle, Direct Mount chain ring, S size: 170mm M size: 170mm L size: 175mm XL size: 175mm, CL 52

Rings

32T, steel, X-Sync 2

•

Bottom bracket

Sram DUB BSA, sealed bearings, 73mm

Chain

Sram SX Eagle, 12s, Powerlock

-

Rear derrailleur

Sram SX Eagle, Type 3 roller bearing clutch, cage lock, long cage, 1x12s, X-actuation 1:1

Shift levers

Sram Trigger SX Eagle, 12s, X-Actuation 1:1

-

Casette

Sram PG-1210, 11-50T, 12s

Derrailleur hanger

Sram UDH

-

Weight

15,9 kg