

COMPONENTS

TECHNICAL SPECS

-

Frame

Raze 29 6061 Alloy Stealth Evo, hydroformed tubing, Zero Suspension System, 130mm travel, Forward Geometry, one piece Monoblock upper link, Boost 12x148mm rear axle, tapered head tube, 73mm BSA bottom bracket, dedicated 1x drivetrain design, telescopic seatpost internal routing, MAX capacity sealed bearings, ISCG 05

Sizes

S: 380mm / M: 420mm / L: 470mm / XL: 510mm

Rear shock

Fox Float EVOL Performance, 205x57.5mm. Settings: 2-position compression adjustment (Open/Firm), rebound, air preload. Trunnion top mount, 25x8mm bottom bushings

Shock settings

Light compression, light rebound, air volume spacer 0.6

Fork

Fox 36 29 Float GRIP EVOL Rhythm, 150mm, tapered steerer tube, Boost 15x110mm axle, offset 44mm. Settings: sweep adjust compression, low-speed rebound, air preload

Headset

Onoff Saturn tapered for 1-1/8" to 1-1/2" head tube, ACB sealed bearings, top 41x30.2x7x45°x45°, bottom 51.9x40x8x45°x45°

Stem

Onoff Sulfur FG 30mm 0°, 6061 forged alloy, 31.8mm barbare

Handlebar

Onoff Sulfur 1.0 double butted 6061 alloy, rise: 20mm, width: 800mm, 9° backsweep, 5° upsweep, 31.8mm barbare

Grips

Onoff Twin, 1lock-on, 135mm

Seatpost

Onoff Pija dropper internal, diameter 31.6mm, 1X Remote lever with bearing, S size: 405x95-125mm, M size: 458x120-150mm, L size: 498x140-170mm, XL size: 558x170-200mm

Saddle

Mondraker MDK Series, SRX, steel rail

Front brake

Sram G2 R, 4-piston caliper, Centerline 180mm IS 6 bolts one-piece rotor, steel-backed organic pads

Rear brake

Sram G2 R, 4-piston caliper, Centerline 180mm IS 6 bolts one-piece rotor, steel-backed organic pads

Brake lever

Sram G2 R, tool-free reach adjust, lever pivot bushings

Rims

Mavic CrossMax XL S, 29 Boost 30mm internal width, hookless, tubeless ready, 24 spokes

Spokes

Mavic 24 straight-pull double butted spokes

Front hub

Mavic Infinity hub, Boost 15x110mm, IS 6 bolts

Rear hub

Mavic Infinity hub, ID360 freewheel technology, Boost 12x148mm, IS 6 bolts, HG freehub

Front tire

Maxxis Dissector 29x2.4 WT, tubeless ready, 3C MAXX TERRA compound, EXO+ protection, 120TPI, folding bead

Rear tire

Maxxis Aggressor 29x2.3, tubeless ready, dual compound, Exo protection, 60TPI, folding bead

Crankset

Truvativ Stylo 7k Eagle, Boost, DUB axle, Direct mount chain ring, S size: 170mm M size: 170mm L size: 175mm XL size: 175mm, CL 52

Rings

32T, CNC-machined alloy, X-SYNC 2

Bottom bracket

Sram DUB BSA, sealed bearings, 73mm

Chain

Sram NX Eagle, 12s, Powerlock

Rear derrailleur

Sram GX Eagle, Type 3 roller bearing clutch, cage lock, 1x12s, X-Actuation 1:1

Shift levers

Sram Trigger NX Eagle, 12s, X-Actuation 1:1

Casette

Sram PG-1230, 11-50T, 12s

Derrailleur hanger

Sram UDH

Weight

15,4 kg