

Compare Models

Amflow PX Carbon

Amflow PX Carbon Pro

Frame

Amflow PX Carbon Frame

Amflow PX Carbon Pro Frame

Phantom Black

Moonstone Gray

40 adjustable geometry configurations

40 adjustable geometry configurations

Compatible with 27.5" and 29" rear

wheels

Compatible with 27.5" and 29" rear

wheels

E-Bike System

Avinox M2S Drive Unit: Nominal

130N·m, Peak 150N·m

Avinox M2S Drive Unit: Nominal

130N·m, Peak 150N·m

Avinox Screen: 2-inch OLED Control

Display

Avinox Screen: 2-inch OLED Control

Display

Avinox Integrated Battery: 700Wh

Avinox Integrated Battery: 700Wh

Avinox Wireless Controllers: Right and

left sides

Avinox Wireless Controllers: Right and

left sides

Avinox Fast Charger: 12A/508W

Avinox Fast Charger: 12A/508W

Rear shock

FOX Float X Performance (MY 2027)

FOX Float X Factory (MY 2027)

2-position lever, custom tune, LSR

adjustment, 210×55mm, air shock

2-position lever, custom tune, LSC &

LSR adjustment, 210×55mm, air shock

Fork

FOX 36 Performance (MY 2027)

FOX 36 Factory (MY 2027)

160mm travel, GRIP damper, Sweep/LSR

adjustment, 15×110mm, 44mm offset

160mm travel, GRIP X2 damper,

HSC/LSC/HSR/LSR adjustment,

15×110mm, 44mm offset

Drivetrain

Rear Derailleur: SRAM S1000 Eagle

Transmission Derailleur

Rear Derailleur: SRAM X0 Eagle

Transmission Derailleur

Chainring: SRAM Eagle Transmission

DM Chainring 38T for Avinox

Chainring: SRAM Eagle Transmission

DM Chainring 38T for Avinox

Shift Levers: SRAM AXS Pod Controller

Shift Levers: SRAM AXS Pod Rocker

Controller

Cassette: SRAM XS-1270 Eagle

Transmission Cassette 10-52T

Cassette: SRAM XS-1295 Eagle
Transmission Cassette 10-52T
Chain: SRAM Eagle 70 Transmission
Flattop Chain
Chain: SRAM X0 Eagle Transmission
Chain
Power Supply: Avinox M2 Series
Electronic Rear Derailleur Power Cable
(SRAM AXS Extension Cord)
Power Supply: Avinox M2 Series
Electronic Rear Derailleur Power Cable
(SRAM AXS Extension Cord)
Crankset: Avinox SL Crank (M/L: 155mm;
XL/XXL: 160mm)
Crankset: Avinox SL Crank (M/L: 155mm;
XL/XXL: 160mm)

Brakes

Magura Gustav Pro Hydraulic Disc
Brake, 4-piston calipers
Magura Gustav Pro Hydraulic Disc
Brake, 4-piston calipers
Magura Sensor Rotor (203mm, 2.5mm)
Magura Sensor Rotor (203mm, 2.5mm)
Amflow Dropper Remote Lever
Mounting Bracket

Wheels

Amflow XMA-30 Mullet Version
Amflow XMC-30 Mullet Version
Front Rim: Alloy, 29", 30mm inner width,
32H, tubeless ready
Front Rim: Carbon, 29", 30mm inner
width, 28H, tubeless ready

Rear Rim: Alloy, 27.5", 30mm inner
width, 32H, tubeless ready
Rear Rim: Carbon, 27.5", 30mm inner
width, 32H, tubeless ready
Spokes: SAPIM E-Light
Spokes: SAPIM E-Light
Front Hub: Alloy, 2 sealed bearings,
15×110mm thru-axle, 32H, 6-bolt
Front Hub: Alloy, 2 sealed bearings,
15×110mm thru-axle, 28H, J-bend, 6-
bolt
Rear Hub: Alloy, 4 sealed bearings,
12×148mm thru-axle, 32H, 6-bolt, 4
pawls 36T, HG
Rear Hub: Alloy, 4 sealed bearings,
12×148mm thru-axle, 32H, J-bend, 6-
bolt, 6 pawls 60T, XD

Tires

Front: Schwalbe Magic Mary, 29×2.5
Gravity Pro, Radial
Front: Schwalbe Magic Mary, 29×2.5
Gravity Pro, Radial
Rear: Schwalbe Albert, 27.5×2.5 Gravity
Pro, Radial
Rear: Schwalbe Albert, 27.5×2.5 Gravity
Pro, Radial

Handlebar

Amflow Enduro Alloy Handlebar
Amflow Enduro Carbon Handlebar
40mm Rise, 800mm Width, 35mm
Diameter

40mm Rise, 800mm Width, 35mm
Diameter

5-degree upsweep, 9-degree
backsweep

5-degree upsweep, 9-degree
backsweep

Grips

Amflow Enduro Grip 2 Lock-on Grips

Amflow Enduro Grip 2 Lock-on Grips

Stem

Amflow Mountain Bike Split Stem

Amflow Mountain Bike Split Stem

Length: 35mm

Length: 35mm

Clamping Diameter: 35mm

Clamping Diameter: 35mm

Saddle

Amflow Mountain Saddle

Amflow Mountain Saddle Titanium

Dropper Post

Amflow Dropper Post Shim (adjustable
travel: 0/5/10/15/20/25mm)

Amflow Dropper Post Shim (adjustable
travel: 0/5/10/15/20/25mm)

M/L Frame: 190mm

M/L Frame: 190mm

XL Frame: 210mm

XL Frame: 210mm

XXL Frame: 230mm

XXL Frame: 230mm

Accessories

Avinox Front Light

Avinox Front Light

Amflow Bottle Cage

Amflow Bottle Cage

Three Geometry Adjustment Systems
(0.5°/1° Headset Cups, Chainstay Flip-
Chip)

Three Geometry Adjustment Systems
(0.5°/1° Headset Cups, Chainstay Flip-
Chip)

5/10mm Dropper Post Travel Reducing
Spacer

5/10mm Dropper Post Travel Reducing
Spacer

Rear Light

Rear Light

Torque Wrench

Torque Wrench

Clear Frame Protection Film

Clear Frame Protection Film

Shock Pump

Shock Pump

Quick Start Guide

Quick Start Guide

IoT Nano SIM Card

Schwalbe Klik Valve Conversion Set

FOX 36 Mud Guard (Short)